

 <p style="text-align: center;">SECT. A-A</p> <p style="text-align: center;">IMPRESSION-STAMP TOOL NO. USING .25 FIGURES</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="4" style="text-align: center;">REVISIONS</th> </tr> <tr> <th>REV</th> <th>DESCRIPTION</th> <th>DATE</th> <th>APPROVED</th> </tr> </thead> <tbody> <tr><td></td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td></td><td></td></tr> </tbody> </table> <p style="text-align: center;">NOTES</p> <ol style="list-style-type: none"> 1. BREAK EDGES .015R OR .015 X 50°-40° EXCEPT WHERE NOTED OTHERWISE. 2. HEAT TREAT TO 145-165 KSI ~ R_c 32-37. CHECK HARDNESS ON INDICATED SURFACE. 3. SEE DWG 412-049-100 FOR TOOL APPLICATION. 4. ALL UNSPECIFIED SURFACES <input checked="" type="checkbox"/> A B .010 	REVISIONS				REV	DESCRIPTION	DATE	APPROVED																																																																																		
REVISIONS																																																																																											
REV	DESCRIPTION	DATE	APPROVED																																																																																								
<p style="writing-mode: vertical-rl; transform: rotate(180deg);">DWG NO: T103167</p> <p style="writing-mode: vertical-rl; transform: rotate(180deg);">REV: S</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;">QTY</td> <td style="width: 10%;">PART OR IDENTIFYING NO</td> <td style="width: 10%;">CODE IDENT NO</td> <td style="width: 10%;">NOMENCLATURE OR DESCRIPTION</td> <td style="width: 10%;">STOCK SIZE</td> <td style="width: 10%;">MATERIAL</td> <td style="width: 10%;">MATERIAL SPEC</td> <td style="width: 10%;">TENSILE STRENGTH 1000 PSI MIN. 100000</td> <td style="width: 10%;">CHEM. ANALYSIS C 0.25-0.35</td> <td style="width: 10%;">FINISH CODE 299-099-031</td> </tr> <tr> <td>1</td> <td>T103167</td> <td></td> <td>PLATE</td> <td>3 3/4 DIA X 1.62</td> <td>4340 STEEL</td> <td>COMMERCIAL</td> <td>CB2</td> <td></td> <td></td> </tr> <tr> <td colspan="10" style="text-align: center;">PARTS LIST</td> </tr> <tr> <td colspan="10" style="text-align: center;">EWA 412M 1.07 W.O. 4720</td> </tr> <tr> <td colspan="10" style="text-align: center;">Bell Helicopter TEXTRON Division of Textron Inc</td> </tr> <tr> <td colspan="10" style="text-align: center;">TITLE: THRUST PLATE - MAST BEARING INSTALLATION & REMOVAL</td> </tr> <tr> <td colspan="10" style="text-align: center;">DWG NO: T103167</td> </tr> <tr> <td colspan="10" style="text-align: center;">D 97499</td> </tr> <tr> <td colspan="10" style="text-align: center;">SCALE 1/1 ISSUED SHEET 1 OF 1</td> </tr> </table> <p style="text-align: right;">(N) 91101</p>		QTY	PART OR IDENTIFYING NO	CODE IDENT NO	NOMENCLATURE OR DESCRIPTION	STOCK SIZE	MATERIAL	MATERIAL SPEC	TENSILE STRENGTH 1000 PSI MIN. 100000	CHEM. ANALYSIS C 0.25-0.35	FINISH CODE 299-099-031	1	T103167		PLATE	3 3/4 DIA X 1.62	4340 STEEL	COMMERCIAL	CB2			PARTS LIST										EWA 412M 1.07 W.O. 4720										Bell Helicopter TEXTRON Division of Textron Inc										TITLE: THRUST PLATE - MAST BEARING INSTALLATION & REMOVAL										DWG NO: T103167										D 97499										SCALE 1/1 ISSUED SHEET 1 OF 1									
QTY	PART OR IDENTIFYING NO	CODE IDENT NO	NOMENCLATURE OR DESCRIPTION	STOCK SIZE	MATERIAL	MATERIAL SPEC	TENSILE STRENGTH 1000 PSI MIN. 100000	CHEM. ANALYSIS C 0.25-0.35	FINISH CODE 299-099-031																																																																																		
1	T103167		PLATE	3 3/4 DIA X 1.62	4340 STEEL	COMMERCIAL	CB2																																																																																				
PARTS LIST																																																																																											
EWA 412M 1.07 W.O. 4720																																																																																											
Bell Helicopter TEXTRON Division of Textron Inc																																																																																											
TITLE: THRUST PLATE - MAST BEARING INSTALLATION & REMOVAL																																																																																											
DWG NO: T103167																																																																																											
D 97499																																																																																											
SCALE 1/1 ISSUED SHEET 1 OF 1																																																																																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2" style="width: 30%;">SOURCES QUALIFIED AND APPROVED BY BHT FOR STANDARDS AND MATERIALS ARE LISTED IN REPORT 299-099-900</td> <td colspan="2" style="width: 30%;">UNLESS OTHERWISE SPECIFIED</td> <td colspan="2" style="width: 40%;">HEAT TREAT BPS 4140</td> </tr> <tr> <td colspan="2">FOR APPROVED INTERCHANGEABLE EQUIVALENTS AND SUPERSEDED PARTS - SEE BHT STANDARD 170-001</td> <td colspan="2">1 MARK PER BPS 4050 2 BREAK ALL CHAMFERED EDGES 3 .015 X 45° OR .015 R 4 TORQUE PER BPS 4018 5 SAFETY PER BPS 4044 6 DIMENSIONAL LIMITS APPLY AFTER PLATING</td> <td colspan="2">DRAWN BY STAPPER 10-26-78 CHECKED BY <i>John</i> 10-26-78 STRESS RELIEF 10-26-78 WEIGHTS 10-26-78 GROUP ENGR <i>John</i> 10-26-78 OS RE 1500 10-26-78 DER 10-26-78</td> </tr> <tr> <td colspan="2">PROPRIETARY RIGHTS NOTICE THESE DATA ARE PROPRIETARY TO BELL HELICOPTER TEXTRON. DISCLOSURE, REPRODUCTION, OR USE OF THESE DATA FOR ANY PURPOSE IS FORBIDDEN WITHOUT WRITTEN AUTHORIZATION FROM BELL HELICOPTER TEXTRON.</td> <td colspan="2">ABBREVIATIONS PER MIL-STD-12 DIMENSIONING AND TOLERANCING TEST NO. E0412A21 DASH. NEXT ASSY USED ON NO. APPLICATION</td> <td colspan="2">TOLENCES ON DECIMALS ANGLES XXX .010 ± 12° XX .010 ± 12° X .010 ± 12° DEG</td> </tr> <tr> <td colspan="2">THE FOREGOING DOES NOT APPLY TO VENDOR PARTS</td> <td colspan="2">ELECTRICAL SYSTEMS PER ANSI Y14.5-1973 PER ANSI Y32.2 ELECTRICAL REF DESIGNATIONS PER ANSI Y32.16</td> <td colspan="2">SURFACE ROUGHNESS PER ANSI B46.1 125 V MACHINED SURFACES EXCEPT AS NOTED PER ANSI Y32.16</td> </tr> </table>		SOURCES QUALIFIED AND APPROVED BY BHT FOR STANDARDS AND MATERIALS ARE LISTED IN REPORT 299-099-900		UNLESS OTHERWISE SPECIFIED		HEAT TREAT BPS 4140		FOR APPROVED INTERCHANGEABLE EQUIVALENTS AND SUPERSEDED PARTS - SEE BHT STANDARD 170-001		1 MARK PER BPS 4050 2 BREAK ALL CHAMFERED EDGES 3 .015 X 45° OR .015 R 4 TORQUE PER BPS 4018 5 SAFETY PER BPS 4044 6 DIMENSIONAL LIMITS APPLY AFTER PLATING		DRAWN BY STAPPER 10-26-78 CHECKED BY <i>John</i> 10-26-78 STRESS RELIEF 10-26-78 WEIGHTS 10-26-78 GROUP ENGR <i>John</i> 10-26-78 OS RE 1500 10-26-78 DER 10-26-78		PROPRIETARY RIGHTS NOTICE THESE DATA ARE PROPRIETARY TO BELL HELICOPTER TEXTRON. DISCLOSURE, REPRODUCTION, OR USE OF THESE DATA FOR ANY PURPOSE IS FORBIDDEN WITHOUT WRITTEN AUTHORIZATION FROM BELL HELICOPTER TEXTRON.		ABBREVIATIONS PER MIL-STD-12 DIMENSIONING AND TOLERANCING TEST NO. E0412A21 DASH. NEXT ASSY USED ON NO. APPLICATION		TOLENCES ON DECIMALS ANGLES XXX .010 ± 12° XX .010 ± 12° X .010 ± 12° DEG		THE FOREGOING DOES NOT APPLY TO VENDOR PARTS		ELECTRICAL SYSTEMS PER ANSI Y14.5-1973 PER ANSI Y32.2 ELECTRICAL REF DESIGNATIONS PER ANSI Y32.16		SURFACE ROUGHNESS PER ANSI B46.1 125 V MACHINED SURFACES EXCEPT AS NOTED PER ANSI Y32.16																																																																			
SOURCES QUALIFIED AND APPROVED BY BHT FOR STANDARDS AND MATERIALS ARE LISTED IN REPORT 299-099-900		UNLESS OTHERWISE SPECIFIED		HEAT TREAT BPS 4140																																																																																							
FOR APPROVED INTERCHANGEABLE EQUIVALENTS AND SUPERSEDED PARTS - SEE BHT STANDARD 170-001		1 MARK PER BPS 4050 2 BREAK ALL CHAMFERED EDGES 3 .015 X 45° OR .015 R 4 TORQUE PER BPS 4018 5 SAFETY PER BPS 4044 6 DIMENSIONAL LIMITS APPLY AFTER PLATING		DRAWN BY STAPPER 10-26-78 CHECKED BY <i>John</i> 10-26-78 STRESS RELIEF 10-26-78 WEIGHTS 10-26-78 GROUP ENGR <i>John</i> 10-26-78 OS RE 1500 10-26-78 DER 10-26-78																																																																																							
PROPRIETARY RIGHTS NOTICE THESE DATA ARE PROPRIETARY TO BELL HELICOPTER TEXTRON. DISCLOSURE, REPRODUCTION, OR USE OF THESE DATA FOR ANY PURPOSE IS FORBIDDEN WITHOUT WRITTEN AUTHORIZATION FROM BELL HELICOPTER TEXTRON.		ABBREVIATIONS PER MIL-STD-12 DIMENSIONING AND TOLERANCING TEST NO. E0412A21 DASH. NEXT ASSY USED ON NO. APPLICATION		TOLENCES ON DECIMALS ANGLES XXX .010 ± 12° XX .010 ± 12° X .010 ± 12° DEG																																																																																							
THE FOREGOING DOES NOT APPLY TO VENDOR PARTS		ELECTRICAL SYSTEMS PER ANSI Y14.5-1973 PER ANSI Y32.2 ELECTRICAL REF DESIGNATIONS PER ANSI Y32.16		SURFACE ROUGHNESS PER ANSI B46.1 125 V MACHINED SURFACES EXCEPT AS NOTED PER ANSI Y32.16																																																																																							

SHOP COPY